Reusable up to 40 Times **Strength Indicator Dye**

HEAT BLOCKING PUTIN



the heat shield of the space shuttle. It will block heat to protect valves and sensitive parts from damage during The unique formula contains a special dye that will fade over directions and visit our website

(X)

Maintain your cool®. Wet Rag is a heat blocking compound made from the same materials used in brazing, soldering, and welding. time letting you know it's time to replace the material. Please see

for more information.

DIRECTIONS

Turn off or disconnect

Mold as much putty to

for maximum protection

technics and applications may vary.

safeguard materials to protect if necessary.

nitrogen for added

Caution: Welding

Use additional

protection.

the surface as you can



Braze, Solder, or Weld Allow surface to cool



All done Place putty back into jar

Tip: If putty becomes brittle or dry, wet hands with a small amount of water and remold.



a Family Company Since 1987.



Part # RT400P

OUR STORY

Designed by a service tech for a service tech

Refrigeration Technologies. "As a service technician for over 1111 N. Armando St 17 years, I combined my HVAC/R expertise with my chemistry background to develop a family of products that every technician will want on their truck. Supercool Asia Pacific Ptv Ltd Refrigeration Technologies is the

Ph: (07) 55 494 000 1951

WetRag

HAZARD STATEMENT:

classified as hazardous

Manufactured by:

This product is not

according to GHS.

Anaheim, CA, 92806 USA. Ph: 714-238-9207. See the S.D.S. for more information Distributed in Australia and New Zealand by:

Thank you for purchasing! John Pastorello Founder & CEO

most trusted name for innovative

products in the industry."

12 ounces (340a)

www.refria.com