



Total Corrosion Protection

No Loss of Heat Transfer



Net Wt. 15oz (432g)

BENEFITS

Viper is a clear permanent coil coating and metal protectant that will not affect heat transfer. Our tough epoxy based formula protects all surfaces from salt water, acids, caustics, oxidation, and corrosive environments. The unique spray pattern penetrates deep between the coil fins for total coverage. Please visit our website for more information.

DIRECTIONS



Turn off or Disconnect all power from system.



Clean coil with Viper Brite, Rinse, and allow surface to dry



Always wear protective gloves, goggles, and clothing. Use in well ventilated areas.



Hold the can a few inches away, apply a single coat to the front and back of the coil and all metal parts.



Wait 30-60 minutes for product to dry. A full cure may take longer depending on weather conditions.



Place system back into operation
All done!

OUR STORY

**Designed
by a service tech
for a service tech**

"As a service technician for over 17 years, I combined my HVAC/R expertise with my chemistry background to develop a family of products that every technician will want on their truck. Refrigeration Technologies is the most trusted name for innovative products in the industry."

Thank you for purchasing!

John Pastorello
Founder & CEO

Viper Coil Coating

DANGER: Flammable Liquid and Vapor Cylinder

HAZARD STATEMENTS:

Highly flammable liquid and vapor. Heating may cause a fire or explosion. Contains gas under pressure; may explode if heated. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tool. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing vapors and only use in well ventilated area.

FIRST AID:

Inhalation: Assure fresh air breathing. Allow the victim to rest. **Skin:** Rinse with water/shower. Remove/Take off immediately all contaminated clothing. **Eye:** Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist. **Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Disposal: Dispose of in accordance with your local regulations. Offer container for recycling.

Manufactured for: Refrigeration Technologies, 1111 N. Armando St, Anaheim, CA 92806 USA.

Ph: 714-238-9207. Fax: 714-238-9234. www.refrig.com
24 Hour Emergency Phone Chem-Tel: 1-800-255-3924. International Calls 1-813-248-0585

See the S.D.S. for more information

Distributed in Australia and New Zealand by: Insert Flam Gas Diamond
Supercool Asia Pacific Pty Ltd, ABN: 71 011 044 385, 14 Motorway Circuit, Ormeau, QLD, 4208, Australia. Ph: (07) 5549 4000. Fax: (07) 5549 4004. www.supercool.au Emergency Ph: (07) 5549 4000

Manufactured for:



a Family Company Since 1987.



Part# RT640A



www.refrig.com